

SUNSPEED SYNT RSi SAE 5W-40

100% biosynthetic-based multi-grade engine oil for passenger car petrol and diesel engines.

Description

The new ROWE SUNSPEED is a biosynthetic-based engine oil. ROWE SUNSPEED uses non-mineral base oils with high-performance synthetic hydrocarbon compounds synthesised entirely from plant biomass. The innovative lubricant combines sustainability with impressive performance.

SUNSPEED SYNT RSi SAE 5W-40 has outstanding cold-start properties and exceeds the established CCS standards. A key factor for optimizing fuel consumption. In addition, the formula itself exhibits only minimal evaporation losses, even at very high temperatures, and achieves excellent NOACK ratings. A key criterion for optimised oil consumption and consistent oil quality.

ROWE SUNSPEED delivers top-rate efficiency, particularly for turbochargers, superchargers and hybrids.

Application

SUNSPEED SYNT RSi SAE 5W-40 has been specially developed to meet the needs of today's petrol and diesel vehicles. It is particularly suitable for vehicles with a petrol or diesel engine, with or without turbocharger, and is used for vehicles without extended maintenance intervals. Its cutting-edge concept enables a broad spectrum of applications and ensures safe operation in all operating conditions.

ROWE recommendations

- ACEA A3/B4
- API SN/CF
- MB 229.3/226.5
- Opel GM-LL-A-025/GM-LL-B-025
- Porsche A40
- PSA B71 2296
- Renault RN 0700/0710
- VW 502 00/505 00

Advantages

- conserves fossil resources. Synthetic base oils made from 100% biomass
- fully compatible. Problem-free topping up and refilling of systems containing conventional engine oil
- tested top-rate performance. Recommended for commonly applied standards and specifications
- reduced oil consumption thanks to low evaporation losses
- top-rate efficiency for turbochargers, superchargers and hybrids
- optimised fuel consumption thanks to excellent cold-start properties

Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0.84
Kinematic viscosity KV 100	ASTM D-7042	mm²/s	14,4
Kinematic viscosity KV 40	ASTM D-7042	mm²/s	84,4
Viscosity index	ASTM D2270	-	178
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	246
Pour point	ASTM D-97 / DIN EN ISO 3016	°C	-33
CCS	ASTM D-5293	cP @ °C	4237@-30
Total base number	DIN 51639-1	mgKOH/g	9,30
Noack	ASTM D5800	%	6,1
Renewable Resource Content		%	76

These characteristics are typical for current production. The data does not constitute an assurance of properties or a guarantee of suitability for a specific application. Existing legal provisions and regulations that affect handling and usage of the products must be observed by the recipient of our products. ROWE products are continuously being developed. For this reason, ROWE retains the right to change all technical data in this product information at any time without prior announcement. Our current General Delivery and Payment Conditions apply (www.rowemotoroil.net).