

HIGHTEC ANTIFREEZE COOLANT AN-SF 12+ READY-MIX -25 °C

Revision date: 19.11.2024

Product code: 21048

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

HIGHTEC ANTIFREEZE COOLANT AN-SF 12+ READY-MIX -25 °C

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Radiator antifreeze

1.3. Details of the supplier of the safety data sheet

Company name:	NISMO INTERNATIONAL llc.
Street:	44 - 46 Street 34 A - Naif - Dubai
Place:	Deira, Dubai, UAE.
Telephone:	+971 4 224 9953
E-mail:	info@rowemotoroil.net

1.4. Emergency telephone number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Acute Tox. 4; H302
Skin Irrit. 2; H315
Eye Irrit. 2; H319
STOT RE 2; H373

Full text of hazard statements: see SECTION 16.

2.2. Label elements


Regulation (EC) No 1272/2008

Hazard components for labelling

ethanediol; ethylene glycol
Potassium 3,5,5-trimethylhexanoate

Signal word: Warning

Pictograms:



Hazard statements

H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H373	May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC ANTIFREEZE COOLANT AN-SF 12+ READY-MIX -25 °C

Revision date: 19.11.2024

Product code: 21048

Page 2 of 11

P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P501	Dispose of contents/container to of the disposal according to local regulations.

2.3. Other hazards

following inhalation: Vapour and mist concentrations above the allowable levels or unusually high concentrations may cause irritation to the nose and throat as well as headache, nausea and drowsiness.
After skin contact: Brief contact with the product may cause slight skin irritation. Prolonged contact (e.g. through soaked clothing) may result in serious skin irritation with symptoms such as redness and swelling.
Following eye contact: Conjunctival redness.
after ingestion: Oral ingestion of small amounts causes kidney damage.
Caution if victim vomits: Risk of aspiration!

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
107-21-1	ethanediol; ethylene glycol			30 - < 60 %
	203-473-3	603-027-00-1	01-2119456816-28	
	Acute Tox. 4, STOT RE 2; H302 H373			
93918-10-6	Potassium 3,5,5-trimethylhexanoate			1 - < 2.5 %
	299-890-3			
	Acute Tox. 4, Skin Corr. 1, Eye Dam. 1; H302 H314 H318			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
107-21-1	203-473-3	ethanediol; ethylene glycol	30 - < 60 %
		dermal: LD50 = 10600 mg/kg; oral: ATE = 500 mg/kg	
93918-10-6	299-890-3	Potassium 3,5,5-trimethylhexanoate	1 - < 2.5 %
		oral: LD50 = >= 2000 mg/kg	

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air. Medical treatment necessary.

After contact with skin

Wash with plenty of water. Immediately remove any contaminated clothing, shoes or stockings. Medical treatment necessary.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain

HIGHTEC ANTIFREEZE COOLANT AN-SF 12+ READY-MIX -25 °C

Revision date: 19.11.2024

Product code: 21048

Page 3 of 11

immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings.

5.2. Special hazards arising from the substance or mixture

Non-flammable.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately.

Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Avoid contact with skin, eyes and clothes. Do not breathe mist/vapours/spray.

For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment. Remove persons to safety.

For emergency responders

Wear personal protection equipment (refer to section 8).

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up**For containment**

Stop leak if safe to do so. Cover drains. Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

HIGHTEC ANTIFREEZE COOLANT AN-SF 12+ READY-MIX -25 °C

Revision date: 19.11.2024

Product code: 21048

Page 4 of 11

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.
Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Hints on joint storage

No special measures are necessary.

7.3. Specific end use(s)

Radiator antifreeze

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
107-21-1	1,2-Dihydroxyethane, vapour	20	52		TWA (8 h)	
		40	104		STEL (15 min)	
107-21-1	Ethane-1,2-diol, vapour	20	52		TWA (8 h)	
		40	104		STEL (15 min)	
107-21-1	Ethylene glycol, vapour	20	52		TWA (8 h)	
		40	104		STEL (15 min)	

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
107-21-1	ethanediol; ethylene glycol			
Worker DNEL, long-term	inhalation	local	35 mg/m ³	
Worker DNEL, long-term	dermal	systemic	106 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	local	7 mg/m ³	
Consumer DNEL, long-term	dermal	systemic	53 mg/kg bw/day	

PNEC values

CAS No	Substance	Value
107-21-1	ethanediol; ethylene glycol	
Freshwater		10 mg/l
Freshwater (intermittent releases)		10 mg/l
Marine water		1 mg/l
Freshwater sediment		37 mg/kg
Marine sediment		3,7 mg/kg
Micro-organisms in sewage treatment plants (STP)		199,5 mg/l
Soil		1,53 mg/kg

8.2. Exposure controls

HIGHTEC ANTIFREEZE COOLANT AN-SF 12+ READY-MIX -25 °C

Revision date: 19.11.2024

Product code: 21048

Page 5 of 11



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye protection/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Use of protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	magenta
Odour:	characteristic

Test method

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	not determined
Flammability:	Not readily combustible.
Lower explosion limits:	not determined
Upper explosion limits:	not determined
Flash point:	>110 °C DIN 51758
Auto-ignition temperature:	not determined
Decomposition temperature:	not determined
pH-Value:	~ 7,8
Viscosity / kinematic: (at 40 °C)	~ 2,0 mm²/s
Water solubility:	completely miscible
Solubility in other solvents	not determined
Partition coefficient n-octanol/water:	not determined
Vapour pressure: (at 20 °C)	<0,1 hPa
Density (at 20 °C):	~ 1,04 g/cm³ DIN 51757
Relative vapour density:	not determined
Particle characteristics:	not relevant

HIGHTEC ANTIFREEZE COOLANT AN-SF 12+ READY-MIX -25 °C

Revision date: 19.11.2024

Product code: 21048

Page 6 of 11

9.2. Other information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

none

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if swallowed.

ATEmix calculated

ATE (oral) 1085 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
107-21-1	ethanediol; ethylene glycol				
	oral	ATE mg/kg 500			
	dermal	LD50 mg/kg 10600	Rabbit	GESTIS	
93918-10-6	Potassium 3,5,5-trimethylhexanoate				
	oral	LD50 mg/kg >= 2000	Rat	Study report (1986)	OECD Guideline 401

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (ethanediol; ethylene glycol)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC ANTIFREEZE COOLANT AN-SF 12+ READY-MIX -25 °C

Revision date: 19.11.2024

Product code: 21048

Page 7 of 11

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

11.2. Information on other hazards

Other information

No information available.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

The product is not: Ecotoxic.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
93918-10-6	Potassium 3,5,5-trimethylhexanoate					
	Acute algae toxicity	ErC50 mg/l	189,87	72 h	Raphidocelis subcapitata	Study report (2016)
	Acute crustacea toxicity	EC50 mg/l	>100	48 h	Daphnia magna (Big water flea)	ECHA
						OECD Guideline 201
						OECD Guideline 202

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
93918-10-6	Potassium 3,5,5-trimethylhexanoate			
	OECD 301B	87,9	28	
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
107-21-1	ethanediol; ethylene glycol	-1,36
93918-10-6	Potassium 3,5,5-trimethylhexanoate	-0,47

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

HIGHTEC ANTIFREEZE COOLANT AN-SF 12+ READY-MIX -25 °C

Revision date: 19.11.2024

Product code: 21048

Page 8 of 11

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160114 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; end-of-life vehicles from different means of transport (including off-road machinery) and wastes from dismantling of end-of-life vehicles and vehicle maintenance (except 13, 14, 16 06 and 16 08); antifreeze fluids containing hazardous substances; hazardous waste

List of Wastes Code - used product

160114 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; end-of-life vehicles from different means of transport (including off-road machinery) and wastes from dismantling of end-of-life vehicles and vehicle maintenance (except 13, 14, 16 06 and 16 08); antifreeze fluids containing hazardous substances; hazardous waste

Contaminated packaging

Hazardous waste according to Directive 2008/98/EC (waste framework directive). Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

<u>14.1. UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>14.2. UN proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>14.3. Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>14.4. Packing group:</u>	No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC ANTIFREEZE COOLANT AN-SF 12+ READY-MIX -25 °C

Revision date: 19.11.2024

Product code: 21048

Page 9 of 11

Information according to Directive
2012/18/EU (SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile
work protection guideline' (94/33/EC).

Water hazard class (D):

1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 2,9,11.

HIGHTEC ANTIFREEZE COOLANT AN-SF 12+ READY-MIX -25 °C

Revision date: 19.11.2024

Product code: 21048

Page 10 of 11

Abbreviations and acronyms

Acute Tox: Acute toxicity
Skin Irrit: Skin irritation
Skin Corr: Skin corrosion
Eye Dam: Eye damage
Eye Irrit: Eye irritation
STOT RE: Specific target organ toxicity - repeated exposure
ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
ATE: Acute toxicity estimate
LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-concentration factor
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative
RID: Regulations concerning the international carriage of dangerous goods by rail
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation
intérieures)
EmS: Emergency Schedules
MFAG: Medical First Aid Guide
ICAO: International Civil Aviation Organization
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container
SVHC: Substance of Very High Concern
For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety
assessment, chapter R.20 (Table of terms and abbreviations).

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Acute Tox. 4; H302	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT RE 2; H373	Calculation method

Relevant H and EUH statements (number and full text)

H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC ANTIFREEZE COOLANT AN-SF 12+ READY-MIX -25 °C

Revision date: 19.11.2024

Product code: 21048

Page 11 of 11

H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H373	May cause damage to organs through prolonged or repeated exposure.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)