

HIGHTEC SYNT RSi SAE 5W-40

Revision date: 27.07.2023

Product code: 20068

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

HIGHTEC SYNT RSi SAE 5W-40

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Motor oil

1.3. Details of the supplier of the safety data sheet

Company name:	NISMO INTERNATIONAL llc.
Street:	44 - 46 Street 34 A - Naif - Dubai
Place:	Deira, Dubai, UAE.
Telephone:	+971 4 224 9953
E-mail:	info@rowemotoroil.net

1.4. Emergency telephone number:**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture**

Regulation (EC) No 1272/2008

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard statements

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P103	Read carefully and follow all instructions.
P273	Avoid release to the environment.
P501	Dispose of contents/container to of the disposal according to local regulations.

2.3. Other hazards

The mixture contains the following substances fulfilling the PBT criteria according to REACH, annex XIII:
Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Propyl)esters,zinc salts.
Endocrine disrupting properties: phenol, (tetrapropenyl) derivatives.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC SYNT RSi SAE 5W-40

Revision date: 27.07.2023

Product code: 20068

Page 2 of 14

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified			60 - < 100 %
	265-157-1	649-467-00-8	01-2119484627-25	
	Asp. Tox. 1; H304			
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified			1 - < 2.5 %
	265-169-7	649-474-00-6	01-2119471299-27	
	Asp. Tox. 1; H304			
68784-26-9	Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized, including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50			1 - < 2.5 %
	701-251-5		01-2119524004-56	
	Aquatic Chronic 4; H413			
84605-29-8	Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Propyl)esters,zinc salts			0.3 - < 1 %
	283-392-8		01-2119493626-26	
	Skin Irrit. 2, Eye Dam. 1, Aquatic Chronic 2; H315 H318 H411			
74499-35-7	phenol, (tetrapropenyl) derivatives			< 0.1 %
	616-100-8	604-092-00-9		
	Repr. 1B, Skin Corr. 1C, Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 1; H360F H314 H318 H400 H410			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64742-54-7	265-157-1	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified	60 - < 100 %
		dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
64742-65-0	265-169-7	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified	1 - < 2.5 %
		dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
68784-26-9	701-251-5	Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized, including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50	1 - < 2.5 %
		dermal: LD50 = > 15000 mg/kg; oral: LD50 = > 5000 mg/kg	
84605-29-8	283-392-8	Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Propyl)esters,zinc salts	0.3 - < 1 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = 4468 mg/kg Skin Irrit. 2; H315: >= 6,25 - 100 Eye Dam. 1; H318: >= 12,5 - 100 Eye Irrit. 2; H319: >= 10 - < 12,5	
74499-35-7	616-100-8	phenol, (tetrapropenyl) derivatives	< 0.1 %
		dermal: LD50 = 15000 mg/kg; oral: LD50 = 2200 mg/kg Aquatic Acute 1; H400: M=10 Aquatic Chronic 1; H410: M=10	

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air.

HIGHTEC SYNT RSi SAE 5W-40

Revision date: 27.07.2023

Product code: 20068

Page 3 of 14

After contact with skin

Wash with plenty of water. Take off contaminated clothing and wash it before reuse.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

After ingestion

Rinse mouth immediately and drink 1 glass of water.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings.

5.2. Special hazards arising from the substance or mixture

Non-flammable.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Avoid contact with skin, eyes and clothes. Do not breathe mist/vapours/spray.

For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment.

For emergency responders

Wear personal protection equipment (refer to section 8).

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up**For containment**

Stop leak if safe to do so. Cover drains. Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

HIGHTEC SYNT RSi SAE 5W-40

Revision date: 27.07.2023

Product code: 20068

Page 4 of 14

Advice on safe handling

No special measures are necessary.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Advice on general occupational hygiene

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff. Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed.

Hints on joint storage

No special measures are necessary.

7.3. Specific end use(s)

Motor oil

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC SYNT RSi SAE 5W-40

Revision date: 27.07.2023

Product code: 20068

Page 5 of 14

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified			
Worker DNEL, long-term	inhalation	local	5,58 mg/m ³	
Worker DNEL, long-term	dermal	systemic	0,97 mg/kg bw/day	
Worker DNEL, long-term	inhalation	systemic	2,73 mg/m ³	
Consumer DNEL, long-term	inhalation	local	1,19 mg/m ³	
Consumer DNEL, long-term	oral	systemic	0,74 mg/kg bw/day	
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified			
Worker DNEL, long-term	inhalation	systemic	2,73 mg/m ³	
Worker DNEL, long-term	inhalation	local	5,58 mg/m ³	
Worker DNEL, long-term	dermal	systemic	0,97 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	local	1,19 mg/m ³	
Consumer DNEL, long-term	oral	systemic	0,74 mg/kg bw/day	
68784-26-9	Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized, including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50			
Worker DNEL, long-term	inhalation	systemic	3,5 mg/m ³	
Worker DNEL, acute	inhalation	systemic	133,6 mg/m ³	
Worker DNEL, long-term	dermal	systemic	8,33 mg/kg bw/day	
Worker DNEL, acute	dermal	systemic	80 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	systemic	0,87 mg/m ³	
Consumer DNEL, acute	inhalation	systemic	0,067 mg/m ³	
Consumer DNEL, long-term	dermal	systemic	4,2 mg/kg bw/day	
Consumer DNEL, acute	dermal	systemic	40 mg/kg bw/day	
Consumer DNEL, long-term	oral	systemic	0,25 mg/kg bw/day	
Consumer DNEL, acute	oral	systemic	50 mg/kg bw/day	
84605-29-8	Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Propyl)esters,zinc salts			
Worker DNEL, long-term	inhalation	systemic	8,31 mg/m ³	
Worker DNEL, long-term	dermal	systemic	12,1 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	systemic	2,11 mg/m ³	
Consumer DNEL, long-term	dermal	systemic	6,1 mg/kg bw/day	
Consumer DNEL, long-term	oral	systemic	0,24 mg/kg bw/day	
74499-35-7	phenol, (tetrapropenyl) derivatives			
Worker DNEL, long-term	inhalation	systemic	0,053 mg/m ³	
Worker DNEL, long-term	dermal	systemic	0,25 mg/kg bw/day	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC SYNT RSi SAE 5W-40

Revision date: 27.07.2023

Product code: 20068

Page 6 of 14

PNEC values

CAS No	Substance	
Environmental compartment		Value
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified	
Secondary poisoning		9,33 mg/kg
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified	
Secondary poisoning		9,33 mg/kg
68784-26-9	Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized, including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50	
Freshwater		0,5 mg/l
Freshwater (intermittent releases)		5 mg/l
Marine water		0,05 mg/l
Freshwater sediment		1650 mg/kg
Marine sediment		165 mg/kg
Secondary poisoning		11,11 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		1340 mg/kg
84605-29-8	Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Propyl)esters,zinc salts	
Freshwater		0,004 mg/l
Freshwater (intermittent releases)		0,045 mg/l
Marine water		0,0046 mg/l
Freshwater sediment		0,022 mg/kg
Marine sediment		0,002 mg/kg
Secondary poisoning		10,67 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		0,002 mg/kg

8.2. Exposure controls

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Use of protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Avoid release to the environment.

HIGHTEC SYNT RSi SAE 5W-40

Revision date: 27.07.2023

Product code: 20068

Page 7 of 14

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	brown	
Odour:	characteristic	
		Test method
Melting point/freezing point:	not determined	
Boiling point or initial boiling point and boiling range:	not determined	
Flammability:	Not readily combustible.	
Lower explosion limits:	not determined	
Upper explosion limits:	not determined	
Flash point:	>200 °C	DIN ISO 2592
Auto-ignition temperature:	not determined	
Decomposition temperature:	not determined	
pH-Value:	not applicable	DIN 51369
Viscosity / kinematic: (at 100 °C)	~ 14,6 mm²/s	DIN 51562
Water solubility:	practically insoluble	
Solubility in other solvents		
not determined		
Partition coefficient n-octanol/water:	not determined	
Vapour pressure:	<0,1 hPa	calculated.
(at 20 °C)		
Density (at 15 °C):	~ 0,849 g/cm³	DIN 51757
Relative vapour density:	not determined	
Particle characteristics:	not relevant	

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

The product is not: Explosive.

Oxidizing properties

The product is not: oxidising.

Other safety characteristics

Evaporation rate:

not determined

Solid content:

not determined

Pour point:

~ -33 °C DIN ISO 3016

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

none

HIGHTEC SYNT RSi SAE 5W-40

Revision date: 27.07.2023

Product code: 20068

Page 8 of 14

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified				
	oral	LD50 > 5000 mg/kg	Rat	REACH Dossier	OECD 401
	dermal	LD50 > 5000 mg/kg	Rabbit	REACH Dossier	OECD 402
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified				
	oral	LD50 > 5000 mg/kg	Rat	REACH Dossier	OECD 401
	dermal	LD50 > 5000 mg/kg	Rabbit	REACH Dossier	OECD 402
68784-26-9	Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized, including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1986)	OECD Guideline 401
	dermal	LD50 > 15000 mg/kg	Rabbit	Study report (1962)	A group of four albino rabbits of either
84605-29-8	Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Propyl)esters,zinc salts				
	oral	LD50 4468 mg/kg	Rat	Study report (1985)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rabbit	Study report (1980)	OECD Guideline 402
74499-35-7	phenol, (tetrapropenyl) derivatives				
	oral	LD50 2200 mg/kg	Rat	Pre-supplier/manufact urer	OECD 401
	dermal	LD50 15000 mg/kg	Rabbit	Pre-supplier/manufact urer	OECD 402

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

HIGHTEC SYNT RSi SAE 5W-40

Revision date: 27.07.2023

Product code: 20068

Page 9 of 14

STOT-repeated exposure

Based on available data, the classification criteria are not met.
Frequently or prolonged contact with skin may cause dermal irritation.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

Endocrine disrupting properties: phenol, (tetrapropenyl) derivatives.

Other information

No information available.

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified					
	Acute fish toxicity	LL50 mg/l	> 100	96 h	Pimephales promelas (fathead minnow)	REACH Dossier OECD 203
	Acute algae toxicity	ErC50 mg/l	> 100	72 h	Pseudokirchneriella subcapitata	REACH Dossier OECD 201
	Acute crustacea toxicity	EL50 mg/l	> 10000	48 h	Daphnia magna (Big water flea)	REACH Dossier OECD 202
	Fish toxicity	NOEC mg/l	>= 1000	14 d	Oncorhynchus mykiss (Rainbow trout)	REACH Dossier QSAR
	Crustacea toxicity	NOEC mg/l	> 10	21 d	Daphnia magna (Big water flea)	REACH Dossier OECD 211
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified					
	Acute fish toxicity	LL50 mg/l	> 100	96 h	Pimephales promelas (fathead minnow)	REACH Dossier OECD 203
	Acute crustacea toxicity	EL50 mg/l	> 10000	48 h	Daphnia pulex (water flea)	REACH Dossier OECD 202
	Fish toxicity	NOEC mg/l	>= 1000	14 d	Oncorhynchus mykiss (Rainbow trout)	REACH Dossier QSAR
	Algae toxicity	NOEC mg/l	>= 100	3 d	Pseudokirchneriella subcapitata	REACH Dossier OECD 201
84605-29-8	Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl) and iso-Propyl)esters,zinc salts					
	Acute fish toxicity	LL50	4,5 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	Study report (2005) OECD Guideline 203
	Crustacea toxicity	NOEC	0,4 mg/l	21 d	Daphnia magna	Study report (2010) OECD Guideline 211
74499-35-7	phenol, (tetrapropenyl) derivatives					
	Acute crustacea toxicity	EL50 mg/l	0,037	48 h	Daphnia magna (Big water flea)	Pre-supplier/manu facturer
	Crustacea toxicity	NOEC mg/l	0,0037	21 d	Daphnia magna (Big water flea)	Pre-supplier/manu facturer

12.2. Persistence and degradability

The product has not been tested.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC SYNT RSi SAE 5W-40

Revision date: 27.07.2023

Product code: 20068

Page 10 of 14

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified			
	OECD 301B	21 %	28	REACH Dossier
	Not easily bio-degradable (according to OECD-criteria).			
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified			
	OECD 301F	31 %	28	REACH Dossier
	Not easily bio-degradable (according to OECD-criteria).			
74499-35-7	phenol, (tetrapropenyl) derivatives			
	OECD 301B	6 - 25 %	28	Pre-supplier/manufactur er
	Not easily bio-degradable (according to OECD-criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
68784-26-9	Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized, including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50	ca. 9,3
84605-29-8	Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Propyl)esters,zinc salts	0,56

BCF

CAS No	Chemical name	BCF	Species	Source
74499-35-7	phenol, (tetrapropenyl) derivatives	289 - 1601		Pre-supplier/manufacture

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The mixture contains the following substances fulfilling the PBT criteria according to REACH, annex XIII:

Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Propyl)esters,zinc salts.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

130206 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; synthetic engine, gear and lubricating oils; hazardous waste

HIGHTEC SYNT RSi SAE 5W-40

Revision date: 27.07.2023

Product code: 20068

Page 11 of 14

List of Wastes Code - used product

130206 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; synthetic engine, gear and lubricating oils; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Authorisations (REACH, annex XIV):

Substances of very high concern, SVHC (REACH, article 59):
phenol, (tetrapropenyl) derivatives

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 30, Entry 75

Information according to Directive
2012/18/EU (SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC SYNT RSi SAE 5W-40

Revision date: 27.07.2023

Product code: 20068

Page 12 of 14

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D):

2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 1.

HIGHTEC SYNT RSi SAE 5W-40

Revision date: 27.07.2023

Product code: 20068

Page 13 of 14

Abbreviations and acronyms

Asp. Tox: Aspiration hazard
Skin Corr: Skin corrosion
Skin Irrit: Skin irritation
Eye Dam: Eye damage
Repr: Reproductive toxicity
Aquatic Acute: Acute aquatic hazard
Aquatic Chronic: Chronic aquatic hazard
ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
ATE: Acute toxicity estimate
LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-concentration factor
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative
RID: Regulations concerning the international carriage of dangerous goods by rail
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
EmS: Emergency Schedules
MFAG: Medical First Aid Guide
ICAO: International Civil Aviation Organization
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container
SVHC: Substance of Very High Concern
For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H304 May be fatal if swallowed and enters airways.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H318 Causes serious eye damage.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

HIGHTEC SYNT RSi SAE 5W-40

Revision date: 27.07.2023

Product code: 20068

Page 14 of 14

H360F	May damage fertility.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. The above data are intended to describe our product in terms of any safety requirements to be observed. They reflect the state of our current knowledge and experience and shall not be construed as warranted characteristics. Any warranty for accuracy and completeness shall be expressly excluded.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)